

HELIUM HG / He



Leader on the European market, thanks to a portfolio of diverse sources, Air Liquide offers reliable, enduring and safe helium product delivery everywhere in Europe

Air Liquide's Gas Encyclopedia - Pages: 989 - 998

Applications

Fiber optics
Airbags
Leak detection

Transport information

Compressed gases

Proper shipping name	Helium, compressed
UN-Nr	1046
ADR/RID	Class 2
	Classification code 1A



Safety Data Sheets

Compressed gas : N° EIGA061A
Access: <https://be.airliquide.com/>

Physical information

Molecular weight	4 g/mol
Relative density:	
Relative density, gas	0.14 (air=1)
Relative density, liquid	N/A (water=1)
Colour	Colorless
Odor	Odorless
CAS number	7440-59-7

Properties

Hazards identification: In high concentrations may cause asphyxiation

Flammability range: Non-flammable

Personal protection: Ensure adequate ventilation. For full and more detailed information, please consult the Material Safety Data Sheet (MSDS).




Cylinder equipment

Valve fittings

Cylinder: B4 - IS 21.7 x 1.814 right-hand male
Bundle: WW 1 1/8 right-hand male

Shoulder colour:

Brown (RAL 8008)



Product Specifications

Global purity (% Vol. abs) He	Impurities (ppm v/v)		Supply mode	Packaging size	Pressure	Capacity	Product reference
≥ 99,996 %	H ₂ O (5 bar)	≤ 5	Cylinder	20L	200 bar	3,6 m³	I6035M20R2A001
	O ₂	≤ 5	Cylinder	50L	200 bar	9,1 m³	I6035L50R2A001
	N ₂	≤ 20	Bundle	V09*50L	200 bar	82 m³	I6035V09R2A001
			Bundle	V12*50L	200 bar	109 m³	I6035V12R2A001
			Bundle	H27*50L	200 bar	246 m³	I6035H27R2A001

Disclaimer

L'AIR LIQUIDE S.A. and/or its affiliates ("AIR LIQUIDE") are not responsible for the use or consequences of use of the information contained in this Product sheet. AIR LIQUIDE does not hold itself out as recommending the use of the information contained herein or reliance thereon in any way, makes no warranties regarding the information contained in this document and assumes no liability or responsibility in connection with the information or suggestions contained herein. AIR LIQUIDE makes no representations or warranties regarding the completeness of this document and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED INCLUDING, BUT NOT LIMITED TO, WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR USE OR PURPOSE. The information contained in this product sheet is based on the technical information and experience currently available to AIR LIQUIDE. This document should not be confused with regulations (national or European), insurance requirements or codes. Moreover it should not be assumed that every acceptable local grade, test or safety procedure or method, precaution, equipment or device is contained herein, nor that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedures. It is up to users of this document to ensure that they have the latest edition. AIR LIQUIDE may, at its sole discretion, add, delete or change some or all of the information contained in this Product sheet. It is strictly forbidden to copy or reproduce some or all parts of this Product sheet without the written authorisation of AIR LIQUIDE. AIR LIQUIDE owns, reserves and retains all proprietary rights, including copyright, to the present Product sheet. This Product sheet and the photographs and images contained herein shall not be copied or reproduced in any way, sold, loaned, transferred or otherwise distributed to others, used for any purpose or in any manner detrimental to the interest of AIR LIQUIDE. The trademarks, service marks, trade names, logos or other indications of origin displayed in this Product sheet are registered and unregistered trademarks of AIR LIQUIDE or a third party from whom AIR LIQUIDE has obtained the right to use them in this Product sheet. Use of any copyright materials and/or trademarks is subject to the written approval of AIR LIQUIDE on a separate permission form.