• Air Liquide

CARBON DIOXIDE / CO₂



Air Liquide's Gas Encyclopedia - Pages: 333 - 368

Applications

Chemical synthesis Cryogenic fluid Inerting agent Protective atmosphere (welding,...) Acidification agent

Transport information

Liquified Gases

 Proper shipping name
 Carbon Dioxide

 UN-Nr
 1013

 ADR/RID
 Class 2

 Classification code 2A

Refrigerated Gases

Proper shipping name UN-Nr ADR/RID Carbon Dioxide 1013 Class 2 Classification code 3A



Safety Data Sheets

Liquefied gas : N° EIGA018A Access: https://be.airliquide.com/ Refrigerated gas : N° EIGA018B Access: https://be.airliquide.com/ Air Liquide is Europe's leading supplier of carbon dioxide and operates more than twenty purification and liquefaction facilities, enabling satisfaction of all customers needs

Physical information

Molecular weight	44.01 g/mol
Relative density:	
Relative density, gas	1.52 (air=1)
Relative density, liquefied Gas	0.82 (water=1)
Relative density, refrigerated Gas	1.03 (water=1)
Colour	Colorless
Odor	Odorless
CAS number	124-38-9

Properties

Hazards identification: Not toxic, but effect on heart rhythm and respiratory rate can appear at 8-10% (or more) concentrations

Flammability range: Non-flammable

Personal protection: Ensure adequate ventilation. For full and more detailed information, please consult the Material Safety Data Sheet (MSDS).



Cylinder equipment

Valve fittings Cylinder: B4 - IS 21.7 x 1.814 right-hand male Bundle: WW 1'1/8 right-hand male

Shoulder colour: Grey (RAL 7037)



Flanders and Brussels: tel +32 (0)3/3039941 e-mail: customerservice.benelux@airliquide.com Wallonia: tel +32 (0)2/7933841 Luxembourg: tel +352 20881137 e-mail: serviceclients.benelux@airliquide.com



Product Specifications

Global purity (% Vol. abs) CO ₂	Impurities (ppm v/v)		Supply mode	Packaging size	Pressure	Capacity	Product reference
≥ 99,7 %	H ₂ O (5 bar)	≤ 200	Cylinder	13L	49.5 bar	10 kg	I5100S13R0A001
			Cylinder	13L DIP TUBE	49.5 bar	10 kg	I5100S13T0A001
			Cylinder	27L	49.5 bar	20 kg	I5100L27R0A001
			Cylinder	27L DIP TUBE	49.5 bar	20 kg	I5100L27T0A001
			Cylinder	50L	49.5 bar	37 kg	I5100L50R0A001
			Cylinder	50L DIP TUBE	49,5 bar	37 kg	I5100L50T0A001
			Bundle	V12*50L	49.5 bar	360 kg	I5100V12R0A001
			Bundle	V12*50L	49.5 bar	360 kg	I5100V12T0A001
			Liquid	-			I5100RG

Air Liquide

Disclaimer

L'AIR LIQUIDE S.A. and/or its affiliates ("AIR LIQUIDE") are not responsible for the use or consequences of use of the information contained in this Product sheet. AIR LIQUIDE does not hold itself out as recommending the use of the information contained herein or reliance thereon in any way, makes no warranties regarding the information contained in this document and assumes no liability or responsibility in connection with the information or suggestions contained herein. AIR LIQUIDE makes no representations or warranties regarding the completeness of this document and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED INCLUDING, BUT NOT LIMITED TO, WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR USE OR PURPOSE. The information contained in this product sheet is based on the technical information and experience currently available to AIR LIQUIDE. This document should not be confused with regulations (national or European), insurance requirements or codes. Moreover it should not be assumed that every acceptable local grade, test or safety procedure or method, precaution, equipment or device is contained herein, nor that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedures. It is up to users of this document to ensure that they have the latest edition. AIR LIQUIDE may, at its sole discretion, add, delete or change some or all of the information contained in this Product sheet. It is strictly forbidden to copy or reproduce some or all parts of this Product sheet without the written authorisation of AIR LIQUIDE. AIR LIQUIDE owns, reserves and retains all proprietary rights, including copyright, to the present Product sheet. This Product sheet and the photographs and images contained herein shall not be copied or reproduced in any way, sold, loaned, transferred or otherwise distributed to others, used for any purpose or in any manner detrimental to the interest of AIR LIQUIDE. The trademarks, service marks, trade names, logos or other indications of origin displayed in this Product sheet are registered and unregistered trademarks of AIR LIQUIDE or a third party from whom AIR LIQUIDE has obtained the right to use them in this Product sheet. Use of any copyright materials and/or trademarks is subject to the written approval of AIR LIQUIDE on a separate permission form.