

# METHANE N55 / CH<sub>4</sub>



Air Liquide's Gas Encyclopedia - Pages: 273 - 303

## Applications

ICP-MS (Dynamic Reaction Cell)

## Transport information

### Compressed gases

Proper shipping name	Methane, compressed
UN-Nr	1971
ADR/RID	Class 2
	Classification code 1F



## Safety Data Sheets

Compressed gas : N° EIGA078A  
Access: <https://be.airliquide.com/>

## Physical information

Molecular weight	16 g/mol
Relative density:	
Relative density, gas	0.6 (air=1)
Colour	Colorless
Odor	Odorless
CAS number	74-82-8

## Properties

**Hazards identification:** Extremely flammable, can cause asphyxiation

**Flammability range:** 4.4 to 17 (% vol in the air)

**Personal protection:** Ensure adequate ventilation. For full and more detailed information, please consult the Material Safety Data Sheet (MSDS).



## Cylinder equipment

### Valve fittings

Cylinder: B8 - W 21.8 x 1.814 left-hand, male

### Shoulder colour:

Red (RAL 3000)



## Product Specifications

Global purity (% Vol. abs)  CH <sub>4</sub>	Impurities (ppm-mol)		Supply mode	Packaging size	Pressure	Capacity	Product reference
≥ 99,9995 %	H <sub>2</sub> O	≤ 2 ppm mol	Cylinder	10L	175 bar	2,2 m³	P0716S10R7A001
	O <sub>2</sub>	≤ 0.5 ppm mol	Cylinder	50L	175 bar	11,2 m³	P0716L50R7A001
	C <sub>2</sub> H <sub>6</sub>	≤ 0.1 ppm mol					
	CnHm other than C <sub>2</sub> H <sub>6</sub>	≤ 0.05 ppm mol					
	CO <sub>2</sub>	≤ 0.1 ppm mol					
	N <sub>2</sub>	≤ 2 ppm mol					
	H <sub>2</sub>	≤ 0.1 ppm mol					

## Disclaimer

L'AIR LIQUIDE S.A. and/or its affiliates ("AIR LIQUIDE") are not responsible for the use or consequences of use of the information contained in this Product sheet. AIR LIQUIDE does not hold itself out as recommending the use of the information contained herein or reliance thereon in any way, makes no warranties regarding the information contained in this document and assumes no liability or responsibility in connection with the information or suggestions contained herein. AIR LIQUIDE makes no representations or warranties regarding the completeness of this document and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED INCLUDING, BUT NOT LIMITED TO, WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR USE OR PURPOSE. The information contained in this product sheet is based on the technical information and experience currently available to AIR LIQUIDE. This document should not be confused with regulations (national or European), insurance requirements or codes. Moreover it should not be assumed that every acceptable local grade, test or safety procedure or method, precaution, equipment or device is contained herein, nor that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedures. It is up to users of this document to ensure that they have the latest edition. AIR LIQUIDE may, at its sole discretion, add, delete or change some or all of the information contained in this Product sheet. It is strictly forbidden to copy or reproduce some or all parts of this Product sheet without the written authorisation of AIR LIQUIDE. AIR LIQUIDE owns, reserves and retains all proprietary rights, including copyright, to the present Product sheet. This Product sheet and the photographs and images contained herein shall not be copied or reproduced in any way, sold, loaned, transferred or otherwise distributed to others, used for any purpose or in any manner detrimental to the interest of AIR LIQUIDE. The trademarks, service marks, trade names, logos or other indications of origin displayed in this Product sheet are registered and unregistered trademarks of AIR LIQUIDE or a third party from whom AIR LIQUIDE has obtained the right to use them in this Product sheet. Use of any copyright materials and/or trademarks is subject to the written approval of AIR LIQUIDE on a separate permission form.